



FEATURES

- ▼ Steel housing with a corrosion resistant white oven-cured polyester powder coat high gloss protective finish.
- ▼ Choice of lamp options in 17w, 20w, 24w, 32w, 40w, and 54w available.
- ▼ 120v AC 60Hz as standard with other options available.
- ▼ Modular recessed luminaires designed to integrate with 300 mm continuous ceiling systems providing mounting options to locate the luminaire parallel or perpendicular to the ceiling panel.
- ▼ Locking lampholders provide resistance to shock and vibration.
- ▼ Choice of diffuser frame colors to match ceiling color.
- ▼ Equipped with a 4 pole terminal block is provided.
- ▼ 5 year warranty.

APPROVALS

- ▼ UL 1598A - Inside Drip Proof Type
- ▼ UL 924 - Emergency Lighting Equipment
- ▼ ABS
- ▼ Conforms to IP 52

APPLICATIONS

- ▼ Marine and wet environments
- ▼ Offshore oil and gas platforms
- ▼ Drill ships and exploration vessels
- ▼ Tankers
- ▼ Corridor and amenity lighting
- ▼ Accommodation areas
- ▼ Control rooms

OPTIONS





To obtain a luminaire with any of the options listed below, please add the following suffix to the part number (not all options can be combined):

- | | |
|--|-------|
| ▼ Emergency Versions (1 lamp) | EM |
| ▼ Red Filter Tube (1 Lamp) | RV-1* |
| ▼ Red Filter Tube (all Lamps) | RV* |
| ▼ Blue Filter Tube (1 Lamp) | BV-1* |
| ▼ Blue Filter Tube (all Lamps) | BV* |
| ▼ 120-277v 50/60 Hz (17, 24, 32 & 54w) | -127 |
| ▼ 220v 50Hz | -225 |
| ▼ 220v 60Hz | -226 |
| ▼ 277v 60Hz | -276 |

* 17w, 20w, 32w & 40w only.

DIMENSIONS

	A	B	C	D	E	F	G	H
17W, 20W, 24W	33 ³ / ₄	24 ¹⁵ / ₁₆	5	28 ¹ / ₂	29 ⁷ / ₁₆	24 ¹⁵ / ₁₆	20	22 ⁵ / ₈
32W, 40W, 54W	57 ¹ / ₂	45 ¹¹ / ₁₆	14 ³ / ₄	52 ¹ / ₄	53 ⁵ / ₈	49 ¹ / ₈	34	46 ¹ / ₄





DAMP/WET LOCATIONS, INSIDE DRIP PROOF FLUORESCENT MODULAR RECESSED CEILING LUMINAIRES

LUMINAIRE TECHNICAL SPECIFICATIONS

HOUSING AND REFLECTOR

Corrosion resistant steel with an off white oven-cured polyester powder coat flat protective finish. The reflector is constructed of copper free aluminum with an off white oven-cured polyester powder coat high gloss protective finish. The diffuser frames can be supplied in a range of colors to match the ceiling.

OUTLETS

All units are supplied with one 1/2" NPT knockout on top.

LAMPHOLDER

Locking lampholders are supplied as standard ensuring positive contact resistance to shock and vibration.

LAMP TYPE

T5, T8 and T12 models use standard lamps dependent on wattage, which are not provided.

BALLAST

Standard luminaires equipped with a High Power Factor (HPF) 120v 60Hz ballast. All ballast electronic with the exception of 20w T12. Magnetic ballasts are available, please contact factory. Other voltage options and emergency ballast also available.

LENS

Supplied with a flat prismatic DR acrylic lens.

TERMINAL BLOCK

Equipped with a 4 pole terminal block is provided.

ORDERING REFERENCES

DRIP PROOF FLUORESCENT CEILING LUMINAIRES				
DESCRIPTION	LAMP TYPE	LAMP SIZE	WEIGHT (lbs)	MODULAR RECESSED
Parallel Type Ceiling Luminaire	F17T8	2 x 17w	14.0	FDA217PAR
	F20T12	2 x 20w	15.0	FDA220PAR
	F24T5/HO	2 x 24w	14.0	FDA224PAR
	F32T8	2 x 32w	23.0	FDA232PAR
	F40T12	2 x 40w	23.0	FDA240PAR
	T54T5/HO	2 x 54w	22.0	FDA254PAR
Perpendicular Type Ceiling Luminaire	F17T8	2 x 17w	15.0	FDA217PER
	F20T12	2 x 20w	16.0	FDA220PER
	F24T5/HO	2 x 24w	15.0	FDA224PER
	F32T8	2 x 32w	25.0	FDA232PER
	F40T12	2 x 40w	25.0	FDA240PER
	T54T5/HO	2 x 54w	24.0	FDA254PER
Parallel Type Ceiling Luminaire	F17T8	3 x 17w	17.0	FDA317PAR
	F20T12	3 x 20w	18.0	FDA320PAR
	F24T5/HO	3 x 24w	17.0	FDA324PAR
	F32T8	3 x 32w	26.0	FDA332PAR
	F40T12	3 x 40w	27.0	FDA340PAR
	T54T5/HO	3 x 54w	26.0	FDA354PAR
Perpendicular Type Ceiling Luminaire	F17T8	3 x 17w	18.0	FDA317PER
	F20T12	3 x 20w	17.0	FDA320PER
	F24T5/HO	3 x 24w	18.0	FDA324PAR
	F32T8	3 x 32w	27.0	FDA332PER
	F40T12	3 x 40w	28.0	FDA340PER
	T54T5/HO	3 x 54w	27.0	FDA354PAR

SPARE PARTS	
LAMPHOLDER	
Locking (17/20/32/40w)	FX4048
T5 HO (24/54w)	FX4064
LENS	
Parallel 17/20/24w	FX2106
Perpendicular 17/20/24w	FX2107
Parallel 32/40/54w	FX2104
Perpendicular 32/40/54w	FX2105
TERMINAL BLOCK	
2 Pole	FX3070
BALLASTS	
1 LAMP	
1 x 17w	FX5173
1 x 20w	FX5009
1 x 24w	FX5307
1 x 32w	FX5173H
1 x 40w	FX5011
1 x 54w	FX5305
2 LAMP	
2 x 17w	FX5173
2 x 20w	FX5001
2 x 24w	FX5307
2 x 32w	FX5260H
2 x 40w	FX5004
2 x 54w	FX5305